



DAVINCI



Specifications ZTT0905 Da Vinci 1500

Available in desk-top and wallmount versions, the DaVinci 1500 is the ultimate in control sophistication, functionality and style.

All DaVinci models feature live full-motion video display, either windowed or full screen, with integral audio. Full-screen external VGA input display is standard on desktop and available as an option on wallmount models.

Revolutionary new software provides unprecedented artistic freedom and easy application development, whether you choose to design on your PC or on the touchscreen itself. Web connectivity via integral 100baseT Ethernet allows quick updates, from anywhere in the world if you wish.

Based on an open-architecture hardware platform and embedded Linux, DaVinci takes advantage of the latest developments in low power consumption PC architecture. 12 volt DC fanless operation (no noise) allows a wide range of installation possibilities.

Wide ranging connectivity lets you use DaVinci as a standalone controller or in conjunction with any of the wide range of CommBox Control Processors.

Panel Type: TFT LCD



Panel Size: 15" / 381mm

Resolution: XGA (1024 x 768 Pixels)

Pixel Pitch: 0.297mm

Brightness: 250cd/m² (Typical)

Contrast Ratio: 400:1 (Typical)

		Address Command Systems Pty Ltd PO Box W105, Warringah Mall NSW 2100 Australia	Telephone +61/2/9938 4811 Fax +61/2/9905 6153	Email sales@commandsys.com.au support@commandsys.com.au www.commandsys.com.au
<small>Command Systems reserves the right to change product specifications at any time for the purpose of product improvement.</small>			<small>Created April 1, 2003. XN908700-096.5XC WERT123490</small>	



Specifications (Contd) ZTT0905 Da Vinci 1500

Viewing Angle H/V: 160°/160°

Display Colour: 262144 Colours

Response Time: 15ms/10ms (Typical)

Inputs: 1 x RGBHV (DB15 connector), 1 x Composite Video, 2 x Audio

Connectivity: IR-Bus, USB, Ethernet, RS-232, RS-422, RS-485



Power Supply: 12Volts @ 3Amps (Supplied via IR-Bus)

Performance: 5 Wire Analogue-resistive touch screen overlay. Embedded Linux controller can be programmed via Ethernet. Internal amplifiers for built in speakers

Dimensions: (WxHxD): 391mm x 396mm x 180mm

Weight: 8.0kg

Tilt Angle: 3°-90°

		Address Command Systems Pty Ltd PO Box W105, Warringah Mall NSW 2100 Australia	Telephone +61/2/9938 4811 Fax +61/2/9905 6153	Email sales@commandsys.com.au support@commandsys.com.au www.commandsys.com.au
<small>Command Systems reserves the right to change product specifications at any time for the purpose of product improvement.</small>			<small>Created April 1, 2003. XN908700-0965XC WERT123490</small>	