



Joey6



Specifications
ZTT0860

Create macros, customise screens (buttons, icons, backgrounds, pictures and control) all from Joey's simple drag and drop style authoring program. Joey Wallmount is able to communicate via direct Infra Red and direct RS232.

This allows the Joey to be a complete control solution. Comes complete with 'Access Port'. A standard single gang size wallplate that provides simple breakout points for IR, RS232 and power. Connects to Joey6 via single Cat5.





Panel Type	Colour LCD, CCFL Backlight.
Panel Size	6.0" diagonal
Resolution	(320xRGB) (W) x 240 (H) pixels
Pixel Size	0.10(W) x 0.34 (H)
Pixel Pitch	0.12 (W) x 0.36 (H)
Effective Viewing Area	117.2 (W) x 88.4 (H) mm
Brightness	250cd/m ² (Typical)
Contrast Ratio	17:1 (Typical)
Display Colour	8 Colour
Touchscreen	Digital 5 x 8 Matrix touchscreen overlay with audio feedback
Effective Viewing Area	119.4 (W) x 90.6 mm
Thickness	2.00mm
Type	Anti-scratch ITO Film over ITO Glass
Power Supply	12V 500mA (supplied for Australia customers only (Can be supplied by IR-Bus).
Front Bezel	Natural anodised aluminum with beveled internal cut and laser etching.

 	<p>Address Command Systems Pty Ltd PO Box W105, Warringah Mall NSW 2100 Australia</p>	<p>Telephone +61/2/9938 4811 Fax +61/2/9905 6153</p>	<p>Email sales@commandsys.com.au support@commandsys.com.au www.commandsys.com.au</p>
<p>Command Systems reserves the right to change product specifications at any time for the purpose of product improvement.</p>		<p>Created April 1, 2003. XN908700:0965XC WERT123490</p>	



Front Bezel Dimensions	193 (w) x 134 (H) x 2 (d) mm
Cut Out Dimensions Joey6	153 (W) x 111 (H) x 50 (D) mm
Chassis Depth	25mm
Dimensions Access Port	68 (W) x 111 (H) x 30 (d) mm
Cut out dimensions	40 (W) x 70 (H) x 35 (D) mm
Weight	800g
Software	Joey Authoring Program
Connectivity (Joey6)	Connects to Access Port Via single Cat5
IR port (connect up to 3 emitters)	Phoenix Connector
RS232	Phoenix Connector
Power	Phoenix Connector
IR Bus	Phoenix Connector
Connectivity (Access Port)	Standard single gang wallplate. Can be fitted either flushmount or in an enclosed wallbox (supplied upon request)
Infra Red Ports (3.5mm Jack)	X 8 (Can run up to 3 emitters from each port)
RS232 Phoenix Connector	X 1 (Can run up to 3 devices from port depending on protocol clash)
Programming port (3.5mm Jack)	X 1
IR Bus Phoenix Connector	X 1
Optional Extras	
IR Blaster	ZTT0833
IR Port Expander	ZTT0813
RS232 Port Expander	ZTT0823
Access Port Wallbox	TBA

 	Address Command Systems Pty Ltd PO Box W105, Warringah Mall NSW 2100 Australia	Telephone +61/2/9938 4811 Fax +61/2/9905 6153	Email sales@commandsys.com.au support@commandsys.com.au www.commandsys.com.au
Command Systems reserves the right to change product specifications at any time for the purpose of product improvement.		Created April 1, 2003. XN908700:0965XC WERT123490	